



RG-ES200 Series

Smart Cloud Managed Switches

Unique Value for CCTV Network



Highlights

- Abundant models fit needs for access layer in SMB network
- Cost-Effective Smart Cloud Managed Switches
- IP Camera Recognition, Unique Value for CCTV Network
- Automatic Loop Prevention Ensures Service Continuity
- Lifetime management on Ruijie Cloud at anytime anywhere

Highlight Features

RG-ES200 Series Switches Gigabit access switch fits the needs in SMB network



802.3at /
802.3af




Abundant Application
Scenarios



Centralized Cloud
Management

Cost-Effective Smart Cloud Managed Switches

ES200 adopts a light-weighted Cloud management design, providing faster response to support richer features.



IP Camera/NVR
recognition



Automatic
Loop Prevention




Mobile VLAN
Configuration



Intelligent
PoE Adaptive

Highlight Features

Unique Value for CCTV Network



250 meters transmission*

Flexible extend mode

IPC Offline Alarm

Individual port reboot

Automatic Loop Prevention Ensures Service Continuity

Network stays connected when network loop happens




Loop Prevention
Detects and prevents loops automatically

Ruijie RY5050C-P

Highlight Features

Cloud, Make Your Business Easy

- SON, zero touch provisioning to Cloud
- Configure VLANs on Ruijie Cloud APP
- Monitor switch statistics at anytime anywhere
- Easy maintenance, save onsite time and cost



Specifications

Basic

Model	RG-ES205GC-P	RG-ES205GC	RG-ES206GC-P	RG-ES208GC	RG-ES209GC-P
10/100/1000Base-T ports	5	5	6	8	9
1000Base-X SFP ports	-	-	-	-	-
PoE/PoE+ ports	4	-	4	-	8
Max. PoE budget	54W	-	54W	-	120W
Layer Type	Layer 2	Layer 2	Layer 2	Layer 2	Layer 2
Switching capacity	10 Gbps	10 Gbps	12 Gbps	16 Gbps	18 Gbps
Forwarding rate	7.44 Mpps	7.44 Mpps	8.93 Mpps	11.90 Mpps	13.39 Mpps
Packet Buffer	1 Mbit	1 Mbit	1 Mbit	1.5 Mbit	1.5 Mbit
MAC address table	2000	2000	4000	4000	4000
Maximum VLAN Support	16	16	16	16	16
Dimensions (W x D x H)	148 mm x 78 mm x 26 mm	119 mm x 75 mm x 24 mm	148 mm x 78 mm x 26 mm	160 mm x 75 mm x 24 mm	202 mm x 108 mm x 28 mm
Weight (With package)	0.9 kg	0.36 kg	0.79 kg	0.49 kg	1.3 kg
MTBF (Hours)	> 200,000	> 200,000	> 200,000	> 200,000	> 200,000
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years

Software Features

10/100/1000M Auto/Full/Half Duplex Negotiation	✓	✓	✓	✓	✓
Flow Control	✓	✓	✓	✓	✓
Storm Suppression	✓	✓	✓	✓	✓
Management IP	10.44.77.200	10.44.77.200	10.44.77.200	10.44.77.200	10.44.77.200
VLAN Range	1 - 4094	1 - 4094	1 - 4094	1 - 4094	1 - 4094
Port-based VLAN	✓	✓	✓	✓	✓

Specifications

Software Features

Model	RG-ES205GC-P	RG-ES205GC	RG-ES206GC-P	RG-ES208GC	RG-ES209GC-P
ACL	-	-	-	-	-
QoS	-	-	-	-	-
ACL	-	-	-	-	-
DHCP Client	✓	✓	✓	✓	✓
DHCP Snooping	✓	✓	✓	✓	✓
Telnet	1 session	1 session	1 session	1 session	1 session
SSH	-	-	-	-	-
DNS Client	✓	✓	✓	✓	✓
SNMP v1/v2/v3	-	-	-	-	-
Many-to-one Port Mirroring	✓	✓	✓	✓	✓
Downlink Loop Protection	✓	✓	✓	✓	✓
Loop Disabled Port	✓	✓	✓	✓	✓
Disconnection Duration	2s	2s	2s	2s	2s
Flow Control	✓	✓	✓	✓	✓
Cable Testing	✓	✓	✓	✓	✓
Web-based Management	✓	✓	✓	✓	✓
HTTP	✓	✓	✓	✓	✓
Cloud Management	✓	✓	✓	✓	✓

Specifications

Hardware Features

Model	RG-ES205GC-P	RG-ES205GC	RG-ES206GC-P	RG-ES208GC	RG-ES209GC-P
Reset Button	Rear	Rear	Rear	Rear	Rear
Cable Hot-swappable	✓	✓	✓	✓	✓
Power Supply Slot	Power adapter	Power adapter	Power adapter	Power adapter	Power adapter
Power Consumption	≤ 60W	≤ 3W	≤ 60W	≤ 4W	≤ 130W
Power Supplies	54V DC adapter, 1.1A	5V DC adapter, 1A	54V DC adapter, 1.1A	5V DC adapter, 1A	54V DC adapter, 2.4A
EEE	-	-	-	-	-
Fan	Fanless	Fanless	Fanless	Fanless	Fanless
Fan Adaptive Speed Adjustment	-	-	-	-	-
Acoustic Noise	Noiseless	Noiseless	Noiseless	Noiseless	Noiseless
Operating Temperature	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	10% to 90% RH	10% to 90% RH	10% to 90% RH	10% to 90% RH	10% to 90% RH
Storage Humidity	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH
Port Surge	4 kV	4 kV	4 kV	4 kV	4 kV
Operating Altitude (meters)	-500 to 5000	-500 to 5000	-500 to 5000	-500 to 5000	-500 to 5000
Certificate	CE, RoHS	CE, RoHS	CE, RoHS	CE, RoHS	CE, RoHS

Package Contents

Device	RG-ES205GC-P	RG-ES205GC	RG-ES206GC-P	RG-ES208GC	RG-ES209GC-P
Power Supply	Power Adapter	Power Adapter	Power Adapter	Power Adapter	Power Adapter
Quick Start Guide	1	1	1	1	1
Warranty Card	1	1	1	1	
Accessories	-	-	-	-	-
Package Weight	0.9 kg	0.36 kg	0.79 kg	0.49 kg	1.3 kg
Package Dimension (w x d x h)	249 mm x 217 mm x 62 mm	178 mm x 158 mm x 52 mm	249 mm x 217 mm x 62 mm	197 mm x 172 mm x 52 mm	305 mm x 289 mm x 64 mm

Device	RG-ES210GC-LP	RG-ES216GC	RG-ES218GC-P	RG-ES224GC	RG-ES226GC-P
Power Supply	Power Adapter	Power cable	Power cable	Power cable	Power cable
Quick Start Guide	1	1	1	1	1
Warranty Card	1	1	1	1	1
Accessories	-	Mounting bracket * 2, Foot pad * 4, Screws * 6	Mounting bracket * 2, Foot pad * 4, Screws * 8	Mounting bracket, Foot pad * 4, Screws * 6	Mounting bracket * 2, Foot pad * 4, Screws * 8
Package Weight	1.38 kg	2.7 kg	3.5 kg	2.8 kg	4.2 kg
Package Dimension (w x d x h)	305 mm x 289 mm x 64 mm	539 mm x 254 mm x 92 mm	419 mm x 301 mm x 123 mm	539 mm x 254 mm x 92 mm	539 mm x 406 mm x 114 mm



Security is within your reach!

Techcom Engineering Pte. Ltd

Address: 2 Yishun Industrial Street 1, #04-11 North Point Bizhub, Singapore 768159

Phone: +65 6677 0000 ; +65 9277 8888

Fax: +65 6339 3688

Email: sales@techcom.co

Website: <https://cctvcamera.sg/>

